

TECHNICAL DATASHEET

RIGA-W1S GU10 IP44 BLACK

08.06.2020

Stock Description: VT/RIGA-W1S/GU10/BLACK/IP44/CLR/220V/SENS/GARDEN

Notes:

General Informations		Electrical Characteristics		Electrical Component Specifications	
Stock Code	3241410	Current Type	AC	Component Fitting Type	N/A
HSC/GTIP Code	9405.10.91.50.00	Operation Voltage	220-240 Volt	Driver Properties	N/A
EAN-13 (Inbox Barcode)		Operation Frequency	50/60 Hertz	Driver Input Voltage	N/A Volt
ITF-14 (Outbox Barcode)		Electrical Current	N/A Amper	Driver Input Current	N/A Amper
Introduction		Power	Max 7 Watt	Driver Output Voltage	N/A Volt
		Power Factor	N/A	Driver Output Current	N/A Amper
		Luminous Efficiency	N/A lumen/Watt	Detection Distance of Sensor	meters
		Energy Savings	N/A	Ballast Properties	N/A
		Ignition Time	N/A seconds	Transformer Properties	N/A
		Dimmable	N/A	Battery Properties	N/A
		Electrical Protection Class	Class I	Battery Charging Time	N/A hours
				Battery Discharge Time	N/A hours
Lighting Characteristics		Mechanical Parameters		Logistic Informations	
Luminous Flux	N/A lumen	Bulb Body Shape	PAR16	Inbox Length	millimeter
Time for 60% of Lumen	N/A seconds	IP Protection Class	IP44	Inbox Width	millimeter
Light Beam Angle	120°	Switch On/Off Cycle	30000	Inbox Height	millimeter
Flicker	N/A	Lifetime	25000 hours	Outbox Length	395 millimeter
LED Type	N/A	Body Material	201 Grade Stainless Steel	Outbox Width	300 millimeter
		Body Colour	Black	Outbox Height	250 millimeter
		Diffuser Material	PC	Outbox Volume	0,02963 m ³
		Reflector Material	N/A	Midbox Quantity	pieces
		Mounting Accessories		Outbox Quantity	12 pieces
		Cut-Hole Sizes	N/A millimeter	Unit Net Weight	0,5 kilogram
		Product Height	290 millimeter	Outbox Net Weight	6 kilogram
		Product Width	60 millimeter	Outbox Gross Weight	8 kilogram

IMPORTANT NOTES: VITO reserves the right to change/remove models or specifications partially/completely without any notice. Information, models and photographs of the products in this technical datasheet can not be used, reproduced or republished without permission. However, some parts can be quoted by giving reference and/or chapter number belonging to technical datasheet. Most of the items in the datasheet have been designed by our company within indicated technical specifications inside. Our company is not responsible for errors caused by wrong installation and operating against rules according to qualifications specified in the product details. Photographs printed in this datasheet may not reflect the actual color of the product depending on printing conditions. In the same context, typographical errors may possibly be found in the texts.