## Stock Description: VT/VEGAS-P1/GU10/BLACK/IP44/220V/OUTWALL FIXTURE

## Notes:

General Informations		Electrical Characteristics		<b>Electrical Component Specifications</b>	
Stock Code	3230310	Current Type	AC	Component Fitting Type	N/A
HSC/GTIP Code	9405.10.91.50.00	Operation Voltage	220-240 Volt	Driver Properties	N/A
EAN-13 (Inbox Barcode)		Operation Frequency	50/60 Hertz	Driver Input Voltage	N/A Volt
ITF-14 (Outbox Barcode) Introduction		Electrical Current	N/A Amper	Driver Input Current	N/A Amper
		Power	Max 7 Watt	Driver Output Voltage	N/A Volt
		Power Factor	N/A	Driver Output Current	N/A Amper
		Luminous Efficiency	N/A lumen/Watt	Detection Distance of Sensor	N/A meters
		Energy Savings	N/A	Ballast Properties	N/A
		Ignition Time	N/A seconds	Transformer Properties	N/A
		Dimmable	N/A	Battery Properties	N/A
		Electrical Protection Class	Class II	Battery Charging Time	N/A hours
				Battery Discharge Time	N/A hours
Lighting Characteristics		Mechanical Parameters		Logistic Informations	
Lighting Ch	naracteristics	Mechanica	Parameters	Logistic Ir	nformations
Luminous Flux	N/A lumen	Mechanical Bulb Body Shape	PAR16	Logistic Ir	nformations millimeter
				_	
Luminous Flux	N/A lumen	Bulb Body Shape	PAR16	Inbox Length	millimeter
Luminous Flux Time for 60% of Lumen	N/A lumen N/A seconds	Bulb Body Shape  IP Protection Class	PAR16	Inbox Length Inbox Width	millimeter
Luminous Flux Time for 60% of Lumen Light Beam Angle	N/A lumen N/A seconds 180°	Bulb Body Shape  IP Protection Class  Switch On/Off Cycle	PAR16 IP44 30000	Inbox Length Inbox Width Inbox Height	millimeter millimeter millimeter
Luminous Flux  Time for 60% of Lumen  Light Beam Angle  Flicker	N/A lumen N/A seconds 180° N/A	Bulb Body Shape  IP Protection Class  Switch On/Off Cycle  Lifetime	PAR16 IP44 30000 25000 hours	Inbox Length Inbox Width Inbox Height Outbox Length	millimeter millimeter millimeter 395 millimeter
Luminous Flux  Time for 60% of Lumen  Light Beam Angle  Flicker	N/A lumen N/A seconds 180° N/A	Bulb Body Shape IP Protection Class Switch On/Off Cycle Lifetime Body Material	PAR16 IP44 30000 25000 hours PP	Inbox Length Inbox Width Inbox Height Outbox Length Outbox Width	millimeter millimeter millimeter 395 millimeter 360 millimeter
Luminous Flux  Time for 60% of Lumen  Light Beam Angle  Flicker	N/A lumen N/A seconds 180° N/A	Bulb Body Shape IP Protection Class Switch On/Off Cycle Lifetime Body Material Body Colour	PAR16  IP44  30000  25000 hours  PP  Black	Inbox Length Inbox Width Inbox Height Outbox Length Outbox Width Outbox Height	millimeter millimeter millimeter 395 millimeter 360 millimeter 280 millimeter
Luminous Flux  Time for 60% of Lumen  Light Beam Angle  Flicker	N/A lumen N/A seconds 180° N/A	Bulb Body Shape IP Protection Class Switch On/Off Cycle Lifetime Body Material Body Colour Diffuser Material	PAR16 IP44 30000 25000 hours PP Black PC	Inbox Length Inbox Width Inbox Height Outbox Length Outbox Width Outbox Height Outbox Volume	millimeter millimeter millimeter 395 millimeter 360 millimeter 280 millimeter 0,03982 m^3
Luminous Flux  Time for 60% of Lumen  Light Beam Angle  Flicker	N/A lumen N/A seconds 180° N/A	Bulb Body Shape IP Protection Class Switch On/Off Cycle Lifetime Body Material Body Colour Diffuser Material Reflector Material	PAR16 IP44 30000 25000 hours PP Black PC	Inbox Length Inbox Width Inbox Height Outbox Length Outbox Width Outbox Height Outbox Volume Midbox Quantity	millimeter millimeter millimeter 395 millimeter 360 millimeter 280 millimeter 0,03982 m^3 pieces
Luminous Flux  Time for 60% of Lumen  Light Beam Angle  Flicker	N/A lumen N/A seconds 180° N/A	Bulb Body Shape  IP Protection Class  Switch On/Off Cycle  Lifetime  Body Material  Body Colour  Diffuser Material  Reflector Material  Mounting Accessories	PAR16  IP44  30000  25000 hours  PP  Black  PC  N/A	Inbox Length Inbox Width Inbox Height Outbox Length Outbox Width Outbox Height Outbox Volume Midbox Quantity Outbox Quantity	millimeter millimeter millimeter 395 millimeter 360 millimeter 280 millimeter 0,03982 m^3 pieces 32 pieces

IMPORTANT NOTES: VITO reserves the right to change/remove models or specifications partially/completely without any notice. Information, models and photographs of the products in this technical datasheet can not be used, reproduced or republished without permission. However, some parts can be quoted by giving reference and/or chapter number belonging to technical datasheet. Most of the items in the datasheet have been designed by our company within indicated technical specifications inside. Our company is not responsible for errors caused by wrong installation and operating against rules according to qualifications specified in the product details. Photographs printed in this datasheet may not reflect the actual color of the product depending on printing conditions. In the same context, typographical errors may possibly be found in the texts.